

# ProLine

## Drying cabinet FC20

### MAIN FEATURES

- Capacity, 6 complete PPE suits
- Automatic & manual programs
- Preset start time
- Temperature & humidity tracking system
- Energy-efficient
- Electric heated air drying
- Dual drying system for efficient and safe PPE drying
- Gentle drying without mechanical action
- Double overheat protection
- Powder coated galvanized steel
- Program ends with 'cool down' mode
- 6 slots for interchangeable hangers with integrated airflows
- Interior lighting
- Versatile hanging options for added convenience



EXTEND THE  
LIFESPAN OF  
YOUR PPE WITH

64%

HTS - Humidity  
Tracking System



Three-year  
limited warranty



Main data	Imperial	Metric		
Product no.		131035		
Interior capacity	cu ft	73	L	2070
Capacity (dry weight)	lb	44	kg	20
Capacity, sets of turnout gear	#	6		

# Technical specifications ProLine FC20

<b>Mail data</b>	<b>Imperial</b>	<b>Metric</b>	
Product No.		131035	
Type		Air vented	
Capacity, sets of suits/overalls	#	6	
Capacity (dry weight)	lb	44	kg 20
Interior capacity	cu ft	73.1	L 2070
Noise emission	dB(A)	65	
<b>Electrical installation</b>			
Supply voltage	V	3~N/400V/50Hz	
Electric heating	W	12000	
Electric fan	W	500	
Total effect	W	12500	
Protection	A	20	
<b>Dimensions</b>			
Outer: width x depth x height	in	71 x 31.5 x 77	mm 1800 x 800 x 1955
Shipping outer: width x depth x height	in	75 x 31 x 42	mm 1915 x 790 x 1060
Door opening	°	190	
Lowest ceiling height in room	in	87	mm 2215
<b>Weight</b>			
Weight	lb	≈441	kg ≈ 200
Shipping weight	lb	≈529	kg ≈ 240
<b>Ventilation</b>			
Outlet exhaust	Ø in	2.36	mm 160
Outlet airflow	cfm	177	m³/h 300
Pressure drop, max	psf	4.4	Pa 210
Maximum airflow (at 0% pressure)	cfm	353	m³/h 600
<b>Drying 6 suits with membrane/liners</b>			
Drying time	min	166	
Drying capacity	oz/min	2	g/min 55
Energy consumption	kWh	19.6	
Residual moisture before drying	%	70	
Residual moisture after drying	%	4	
<b>Drying 6 suits without membrane/liners</b>			
Drying time	min	85	
Drying capacity	oz/min	1.6	g/min 46
Energy consumption	kWh	6.8	
Residual moisture before drying	%	15	
Residual moisture after drying	%	0	

